

ILS-2600-000

L-865(L) LED

White Day/Night System

Visit our website: www.itl-llc.com

The **ILS-2600 Medium Intensity White Obstruction Lighting System** utilizes LED technology and precision optics to provide a low power, low light pollution, tower lighting solution. **All electronics is accessible at ground level** reducing the need for costly tower climbs. The flash head contains only LEDs and a multi-stage surge suppression network. System modularity facilitates maintenance and long term reliability. Low noise design enhances **compatibility with 4G/LTE technology**.



Features

- Precision optical design minimizes both “sky-glow” and “ground-scatter” light pollution.
- **Infrared option** available (ILS-2600-0IR).
- **Multi-stage surge suppression** networks included in the flash head and at ground level.
- Rated for up to **800 ft** of flash head cable.
- No microprocessor or driver electronics above ground level.
- **GPS** synchronization of flash cycle requires only the addition of a GPS antenna (ANT-018X-GPS-KIT).
- Dry contacts (Form-C) provided for White Alarm, Side Light, Photocell, GPS, Power Fail alarms and day/night mode.
- Failure of the photocell to transition results in default to day mode operation.
- Indicator LEDs provided for white alarms, PEC alarm, side light alarm, operating mode, GPS functions and more.
- D2 type systems available.

Specifications

Standards:	ETL Certified to AC150/5345-43, Type L-865 (L)
Temperature:	-40°C to +55°C
Humidity:	Less than 95%, non-condensing
Day Intensity:	20,000 ±25% effective candelas
Night Intensity:	2,000 ±25% effective candelas
Beam Pattern:	360° Horizontal, ≥3° Vertical
Flash Rate:	40FPM Day, 40FPM White Night
Flash Head:	Height: 14.7” (37.4cm), Diameter: 13” (33cm), 33lbs (15Kg)
Power Supply:	23.63”(60.0cm) x 16.57”(42cm) x 9.76”(24.8cm), 40lbs(18.1Kg)
Suppression:	70 Joule, 275V, Input Power, PEC, Side Lights 45 Joule, 275V, All Dry-Contact Alarms
Input Power:	120 or 240 Vac, 50/60 Hz Day: 95W White Night: 35W White/IR Night: 40W (IR option req'd)

